SPC Delex Gold®

rang do india

A Golden Touch to Every Wall





Interior Paints . Exterior Paints . Wall Putty. Cement Paint
Primers - Interior & Exterior. Distemper. Master Care Products

Website: www.delexgold.com I Email Id: info@delexgold.com

SPC Delex Gold®

rang do india

ULTRA PLUS

LUXTERA EXTERIOR PRIMER

बाहरी दीवारों को दो सॉलिड बेस

Kyunki Base Achha, Toh Colour Bhi Achha



Luxtera Exterior Primer

Extra-Coverage Exterior Paint

PRODUCT COMPOSITION & USAGE:

Luxtera Exterior Primer is an extra-coverage exterior primer for outdoor walls. Its upgraded acrylic formula provides a dependable, uniform base that supports better colour payoff and helps topcoats stay brighter over time. The ammonia-free primer offers a clean finish and reliable performance under changing weather conditions.

- **WIDER COVERAGE**
- **RELIABLE BASE COAT**
- **SMOOTH FINISH**
- **BETTER OPACITY & BRIGHTNESS**

SPECIFICATIONS

Product Type	Exterior Primer
Series	Ultra Plus
Finish	Smooth & Even
Formulation	Acrylic
Application	Brush / Roller
Dilution	35–45% with clean water
Recoating Interval	4-6 Hours
Formulation Highlights	Ammonia-Free, Low Odour



SURFACE PREPARATION

Clean surface thoroughly.
Remove loose particles with sand paper or wire brush.
Ensure surface is dry and dust-free.
Repair cracks and holes with crack seal or putty.

For properly prepared exterior wall surfaces before application of a suitable exterior top coat.

Surface: Exterior

Now Available Packs: 1 LTR | 4 LTR | 10 LTR | 20 LTR

SHELF LIFE: 24 Months From date of manufacturing

**Coverage may vary depending on surface porosity and texture.*

SPC
Delex Gold®
rang do india

ULTRA PLUS
ARTSHIELD

बाहरी दीवारों को रंग भी
Protection Bhi



Artshield Exterior Emulsion

Extra-Coverage Exterior Paint

PRODUCT COMPOSITION & USAGE:

Artshield Exterior Emulsion is a water-thinnable exterior emulsion that provides a consistent, extra-coverage coat for exterior walls. Its formulation gives walls a smooth, even finish while providing reliable protection and helping maintain their appearance through changing weather conditions.

- **PREMIUM QUALITY**
- **SMOOTH, EVEN FINISH**
- **4 YRS UP TO 4 YEARS PROTECTION**
- **EXTRA COVERAGE**

SPECIFICATIONS

Product Type	Exterior Emulsion
Series	Ultra Plus
Finish	Smooth & clean
Formulation	Water-Thinnable
Application	Brush / Roller
Dilution	35–45% with clean water
Recoating Interval	4 Hours
Formulation Highlights	Ammonia-Free, Low Odour



SURFACE PREPARATION

Clean surface thoroughly.
Remove loose particles with sand paper or wire brush.
Ensure surface is dry and dust-free.
Repair cracks and holes with crack seal or putty.

Surface: Exterior

Now Available Packs: 1 LTR | 4 LTR | 10 LTR | 20 LTR

SHELF LIFE: 24 Months From date of manufacturing

**Coverage may vary depending on surface porosity and texture.*

SPC Delex Gold®

rang do india

ULTRA LITE

AQUASHINE

जहाँ सुरक्षा मिले शानदार चमक के साथ।



WOOD. WALL. WALL PAINTING

AQUASHINE

Hi-Gloss Water-Based Enamel

PRODUCT COMPOSITION & USAGE:

Delex Gold Ultra Lite Aquashine Hi-Gloss is a water-based enamel that brings a bright, consistent color tone to your regular spaces. Made for a low-odour, easy application using a brush, roller, or spray, it refreshes walls and wooden surfaces with a vibrant, high-gloss sheen. The quick-drying, stain-resistant finish ensures your surfaces are not only beautiful but also easy to clean, maintaining their fresh look for longer. It is suitable for wood, wall and wall painting only.

- INTERIOR & EXTERIOR USE
- SMOOTH, GLOSSY FINISH
- CONSISTENT COLOUR TONE
- LOW ODOUR

SPECIFICATIONS

Product Type	Water-Based Enamel
Series	Ultra Lite
Finish	Smooth & Glossy
Base:	Water-Based
Application	Brush / Roller / Spray
Dilution	5–10% with clean, soft, or 100% filtered water
Recoating Interval	4-6 Hours
Formulation Highlights	Ammonia-Free, Low Odour



SUITABLE SURFACE

Suitable for interior and exterior use on properly prepared walls, masonry, and wooden surfaces.

APPLICATION STEPS:

Prepare: Clean and smooth the surface. Repair any cracks or dents using a suitable putty.
Primer: Apply a suitable water-based primer and allow it to dry completely.
Dilute: Mix the paint with 5–10% clean, soft water.
Apply: Apply the first coat smoothly across the surface.
Recoat: Allow 4 to 6 hours of drying time, then apply a second coat for full coverage and maximum gloss.

www.delexgold.com

Now Available Packs: 1 LTR | 4 LTR | 10 LTR | 20 LTR

SHELF LIFE: 24 Months
From date of manufacturing

SPC Delex Gold®

rang do india

ULTRA LITE

WALLZ SHIELD

मौसम बदले, दीवारों की सुरक्षा नहीं।



WALLZ SHIELD
Acrylic Exterior Emulsion

PRODUCT COMPOSITION & USAGE:

Delex Gold Ultra Lite Wallz Shield is an acrylic exterior emulsion made to handle changing weather conditions. It provides reliable protection against changing weather conditions.It helps your exterior walls look more fresh longer and provides good coverage along with smooth anduniform finish.

- ANTI-ALGAL
- WEATHER RESISTANT
- GOOD COVERAGE
- LOW ODOUR
- 3 YEARS OF STRONG PERFORMANCE

SPECIFICATIONS

Product Type	Exterior Emulsion
Series	Ultra Lite
Finish	Uniform & Clean
Base:	Acrylic
Application	Brush / Roller
Dilution	30–40% with clean, filtered or soft water
Recoating Interval	4 Hours
Suitable Surface	Exterior Walls



SURFACE PREPRATION

1. Ensure the surface is clean, dry, and free from dust, grease, or flaking paint.
2. For uneven surfaces, apply a coat of putty, then primer, and allow it to dry.
3. Sand the surface lightly before painting.

APPLICATION STEPS:

Mix thoroughly before use.
Dilute with 35-40% clean water if needed.
Apply the first coat evenly using a roller or brush.
Keep a 4-hour gap between two coats for better results.

Now Available Packs: 1 LTR | 4 LTR | 10 LTR | 20 LTR

SHELF LIFE: 24 Months From date of manufacturing

www.delexgold.com

SPC Delex Gold®
rang do india

हर दीवार को मिले *Extra* मजबूती



ULTRA PLUS

Putty Booster

Ultra Plus Putty Booster

Putty Ka Performance Karo Aur Mazboot

PRODUCT COMPOSITION & USAGE:

Ultra Plus Putty Booster is a liquid latex-polymer additive designed to improve the quality and performance of wall putty and other compatible cement- and paint-based products. It helps improve putty strength, adhesion and finish while making the putty easier to apply. It can also help reduce cracks, increase working time and improve the strength and durability of compatible paint and primer applications.

- BETTER FINISH
- 2X DOUBLE STRENGTH
- IMPROVED ADHESION
- SMOOTHER WALL SURFACE

SPECIFICATIONS

Product Type	Liquid Additive
Series	Ultra Plus
Base	Latex Polymer
Formulation	Water-Thinnable
Application	Interior & Exterior Surfaces



For Use With:
Wall Putty, Cement Paint, Acrylic Distemper, Cement Primer & Emulsion Paint

HOW TO USE

1. Add Water & Ultra Plus Putty Booster.
2. Mix 500ml of Putty Booster with 20 kg of Wall Putty/Cement Paint/Acrylic Distemper & 20L of W.T. Cement Primer/W.T. Emulsion Paint.
3. Add the solution to the dry putty and mix well.
4. Gradually add the remaining water until the desired consistency is achieved.

Interior & Exterior Surfaces:
Suitable for use with compatible wall putty, cement- and paint-based applications on interior and exterior surfaces.

Surface: Interior, Exterior

Now Available Packs: 1 LTR, 5 LTR

SHELF LIFE: 12 Months
From date of manufacturing

DELEX GOLD

AN ISO 9001:2015 CERTIFIED COMPANY

B.Office- 7th Floor, Plam Court
MG Road, Sector-16. Gurugram-122007 (INDIA)

www.delexgold.com